

ACCU-VIS®

LIQUID DRILLING FLUID POLYMER

DESCRIPTION

ACCU-VIS is a liquid copolymer designed for fast field mixing, viscosity building, and clay/shale stabilization in aqueous drilling fluids. ACCU-VIS is certified to NSF/ANSI Standard 60, Drinking Water Treatment Chemicals - Health Effects.

RECOMMENDED USE

ACCU-VIS can be used to inhibit clay and shale hydration, as well as an additive in bentonite drilling fluids to increase viscosity and lower fluid loss. It may also be used with BELLE CRUMBLES to make a high solids grout.

ACCU-VIS can also be used in drilled shafts. When added into SHORE PAC slurry, ACCU-VIS instantly boosts the viscosity, for improved viscosity, fluid loss control, bit lubrication, and shale stabilization/inhibition. Delivers instant viscosifying performance.

CHARACTERISTICS

- 50% active ingredient
- Can be mixed directly in the borehole or excavation
- Eliminates clay and shale swelling, bit balling, and sticking problems
- Excellent additive with BELLE CRUMBLES for a high solids grout
- Fast mixing
- Forms a tight, thin filter cake in unstable formations
- Improves loading and removal of spoils
- Improves skin friction
- Maintains borehole integrity in horizontal and vertically drilled holes

MIXING AND APPLICATION

When using ACCU-VIS, pre-treat mix water with SODA ASH to a pH above 8.5. Always mix bentonite first and then add ACCU-VIS. To breakdown ACCU-VIS, add 0.5 gallon (2.25 L) of sodium hypochlorite (bleach) per 100 gallons (454 L) of drilling fluid.

When using ACCU-VIS in a SHORE PAC slurry, pre-treat mix water with SODA ASH to a pH above 8.5. Always mix SHORE PAC first and then add ACCU-VIS. To breakdown ACCU-VIS, add 1 gallon (3.8 L) of SLURRY BUSTER per 1,000 gallons (3785 L) of SHORE PAC Slurry.

PACKAGING

44 lb (20 kg) pail, 32 per pallet. All pallets are plastic-wrapped.



ACCU-VIS MIXING RATIOS

TYPICAL APPLICATION

Added to air foam	0.5 quart per 100 gallons foam
Added to bentonite system	0.5 quart per 100 gallons drilling fluid
Added to freshwater	0.5 quart per 100 gallons water
Added to grout system	8 ounces per 24 gallons water and 1 bag/BELLE CRUMBLES
Added to air foam	2 liters per 100 liters foam
Added to bentonite system	2 liters per 100 liters drilling fluid
Added to freshwater	2 liters per 100 liters water
Added to grout system	0.25 liters per 109 liters water and 1 bag/BELLE CRUMBLES

DRILLED SHAFTS

Added to freshwater	1.0 to 2.0 gallons per 1,000 gallons water
Added to boost viscosity	1.0 gallon per 1,000 gallons SHORE PAC slurry
Added to freshwater	3.78 liters to 757 liters water
Added to boost viscosity	3.78 liters per 3785 liters SHORE PAC slurry

North America: 847.851.1800 | 800.527.9948 | www.CETCO.com

© 2014 CETCO. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit www.CETCO.com. CETCO accepts no responsibility for the results obtained through application of this product. CETCO reserves the right to update information without notice.

UPDATED: SEPTEMBER 2013

TDS_ACCU-VIS_AM_EN_201309_v1

CETCO®
OUR STANDARDS. YOUR PEACE OF MIND.
 A Minerals Technologies Company