



CX-U Technical Data



The CX range of piling hammers are designed to operate from standard USA leads or crane suspended. They are suitable for driving a wide variety of bearing and sheet piles. The hammers have the following important features.

- Total control of hammer stroke and blow rate.
- Allows precise matching of energy to pile driving requirements.
- Digital readout of hammer performance in choice of units - (Stroke or Energy)
- Simple, fast dolley changing
- Cylinder and dropweight connection easily accessible
- Cage and dropweight design gives short overall hammer length
- Available with BSP Hydropacks which conform to latest EC emissions regulations
- Can be operated directly from Hydraulic crane or excavator bases.

Model	Ram Mass	Max. Impact Energy	Blow Rate @ rated energy	Basic Hammer Weight, w/o helmet	Basic Hammer Length	Min. USA Leader Size	Operating Pressure	Hydraulic Flow Required
	lbs	Ft.lbs	bpm	lbs	Ft & in	in	psi	US gpm
CX50-u	8,800	35,000	50	15,330	15' 2"	26"	3000	42
(CX60-u)	11,000	43,300	43	18,300	16' 7"	26"	3200	52
CX85-u	15,425	60,000	40	22,700	16' 7"	26"	3400	52
CX110-u	19,850	78,000	36	27,600	19' 1"	32"	3400	55

Performance related to use with BSP Hydropacks.

The Power to Perform

BSP International Foundations Ltd.

Claydon Business Park, Gt. Blakenham Ipswich Suffolk, IP6 0JD, England

Tel. +44 1473 830431, Fax +44 1473 832019, email: sales@bspif.co.uk www.bsp-if.com

BSP: CX-u Hydraulic Hammer Range