

DE-CHLOR™

DECHLORINATION ADDITIVE

DESCRIPTION

DE-CHLOR is a white granular crystal that neutralizes chlorine in municipal water. Chlorine in water supplies can destroy polymer drilling fluids.

RECOMMENDED USE

Pre-treat make-up water with DE-CHLOR prior to mixing polymer drilling fluids to prevent premature breakdown, as well as to extend the yield and recycle life of polymer slurries.

ADVANTAGES

- Boosts performance up to 50% without adding primary polymer
- Economical method for neutralizing chlorine
- Increases slurry life
- Stops chlorine from destroying polymer slurries

CHARACTERISTICS

Appearance	White/off-white granular
Specific Gravity	1.69 lbs/liter
Solubility	50 grams/100 grams cold water

MIXING AND APPLICATION

Add 0.5 lb DE-CHLOR per 1,000 gallons (0.25 kg DE-CHLOR per 3.8 m³) make-up water either through a VENTURI HOPPER or by sprinkling into the flow of water filling the borehole. Mix DE-CHLOR at the same time SODA ASH is added to the make-up water.

PACKAGING

50 lb (22.7 kg) plastic pails, 32 per pallet. All pallets are plastic-wrapped.



North America: 847.851.1800 | 800.527.9948

© 2013 CETCO. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit www.CETCO.com. CETCO accepts no responsibility for the results obtained through application of this product. CETCO reserves the right to update information without notice.

UPDATED: OCTOBER 2013

TDS_DE_CHLOR_AM_EN_201310_v1

CETCO®

An **AMCOL** Company

www.CETCO.com