



Specifications*

Energy Per Blow, Adjustable

Pump Setting 1	61 %	327.4 / 241,470	kNm / ft-lbs
Pump Setting 2	76 %	406.3 / 299,630	kNm / ft-lbs
Pump Setting 3	83 %	443.6 / 327,230	kNm / ft-lbs
Pump Setting 4	100 %	534.5 / 394,250	kNm / ft-lbs
Frequency		36...46	blows/min
Related Piston Stroke		3.4...2.0 / 11.1...6.8	m / ft.

Maximum batter w/o upper cyl. ext.	1:5	-
with upper cylinder extension	1:2	-
Fuel consumption at full load	45.0 / 11.9	L/hr. / gal./hr.
Oil consumption	5.0 / 1.32	L/hr. / gal./hr.

Approx. Weights

Hammer	31200 / 68,785	kg / lbs.
Piston	16000 / 35,275	kg / lbs.
Hammer with standard guiding	33800 / 74,516	kg / lbs.

Capacities

Fuel Tank	238 / 63.0	L / gal.
Oil Tank	80 / 21.1	L / gal.

Dimensions

A	- Length, bare hammer	7864 / 25.8	mm / ft.
LH	- Length, standard	7864 / 25.8	mm / ft.
B	- Center to trip	856 / 33.7	mm / in.
C	- Center to pump guard	622 / 24.5	mm / in.
D	- Width of hammer	1156 / 45.5	mm / in.
D1	- Width of trip	1300 / 51.2	mm / in.
W	- Minimum lead width	1220 / 48	mm / in.

*September 21, 2006 Technical data are subject to change without prior notice
 Operating energy based on piston stroke – values are approximate.
 Hydraulic start optional