



Specifications*

Energy Per Blow, Adjustable

Pump Setting 1	50 %	47.9 / 35,400	kNm / ft-lbs
Pump Setting 2	74 %	70.0 / 51,630	kNm / ft-lbs
Pump Setting 3	90 %	85.4 / 62,920	kNm / ft-lbs
Pump Setting 4	100 %	94.8 / 69,925	kNm / ft-lbs
Frequency		37...52	blows/min
Related Piston Stroke		3.2...1.6 / 10.5...5.3	m / ft.

Maximum batter w/o upper cyl. ext.	1:5	-
with upper cylinder extension	1:1	-
Fuel consumption at full load	10.0 / 2.64	L/hr. / gal./hr.
Oil consumption	1.0 / 0.26	L/hr. / gal./hr.

Approx. Weights

Hammer	6110 / 13,472	kg / lbs.
Piston	3000 / 6,615	kg / lbs.
Hammer with standard guiding	7210 / 15,900	kg / lbs.

Capacities

Fuel Tank	67 / 17.7	L / gal.
Oil Tank	19 / 5.0	L / gal.

Dimensions

A	- Length	5425 / 17.8	mm / ft.
LH	- Length, standard	6490 / 21.3	mm / ft.
	- Length with hydraulic start	6860 / 22.5	mm / ft.
B	- Center to trip	445 / 17.5	mm / in.
B1	- Center to trip with cylinder	610 / 24.0	mm / in.
C	- Center to pump guard	482 / 19.0	mm / in.
D	- Width of hammer	635 / 25.0	mm / in.
D1	- Width of trip	812 / 32.0	mm / in.
W	- Minimum lead width	660 / 26.0	mm / in.

*September 21, 2006 Technical data are subject to change without prior notice
 Operating energy based on piston stroke – values are approximate.
 Hydraulic start and upper cylinder extension optional.