



Specifications*

Energy Per Blow, Adjustable

Pump Setting 1	50 %	29.2 kNm	21,510 ft.lbs.
Pump Setting 2	66 %	38.0 kNm	28,035 ft.lbs.
Pump Setting 3	83 %	47.8 kNm	35,260 ft.lbs.
Pump Setting 4	100 %	57.6 kNm	42,480 ft.lbs.

Frequency 37 - 52 blows/min

Related Piston Stroke 3.2 - 1.6 m 10.5 - 5.3 ft.

Maximum batter w/o upper cyl. ext. 1:5 -

with upper cylinder extension 1:1 -

Fuel consumption at full load 7.6 L/hr. 2.00 gal./hr.

Oil consumption 0.6 L/hr. 0.16 gal./hr.

Approx. Weights

Hammer 3795 kg 8,365 lbs.

Piston 1820 kg 4,015 lbs.

Hammer with standard guiding 4400 kg 9,700 lbs.

Capacities

Fuel Tank 75 L 20.0 gal.

Oil Tank 19 L 5.0 gal.

Dimensions

A - Length 5610 mm 18.4 ft.

LH - Length, standard 5850 mm 19.2 ft.

B - Center to trip 356 mm 14.0 in.

B1 - Center to trip with cylinder 559 mm 21.0 in.

C - Center to pump guard 406mm 16.0 in.

D - Width of hammer 495 mm 19.5 in.

D1 - Width of trip 622 mm 24.5 in.

W - Minimum lead width 534 mm 21.0 in.

*Technical data are subject to change without prior notice

Operating energy based on piston stroke - values are approximate.

Hydraulic start optional.