SLURRY BUSTER™ DRY

SHORE PAC POLYMER SLURRY BREAKER

DESCRIPTION

SLURRY BUSTER DRY is an industrial grade oxidizing agent used to breakdown SHORE PAC polymer slurry. This white granular solid dissolves completely when applied to SHORE PAC polymer slurry. The active ingredient is a powerful class III oxidizer that ensures rapid and complete slurry degradation. SLURRY BUSTER DRY is supplied in plastic re-sealable pails. SLURRY BUSTER DRY is a highly effective clean-up solution.

RECOMMENDED USE

SLURRY BUSTER DRY mixes rapidly into the drilling slurry and breaks the polymer backbone through an oxidation reaction. After treatment with SLURRY BUSTER DRY all that remains is water; ready for convenient disposal. SLURRY BUSTER DRY is designed to be added at the tank or waste pit but never to the excavation.

CHARACTERISTICS

- · No freeze concerns
- Maximum strength at 65% active ingredients
- Easy-to-use re-sealable pails
- · Breaks slurry faster for quick, efficient disposal
- · Soluble in water
- · Will not decompose when stored of properly

TYPICAL PROPERTIES

Physical State: Solid Granular
Appearance: White to off white
Odor: Chlorine-like

pH: 10.4 - 10.8 (1% solution in neutral, distilled

water) (@ 25° C)

MIXING AND APPLICATION

15 lbs of SLURRY BUSTER DRY per 10,000 gallons SHORE PAC polymer slurry. Circulate entire volume of slurry by pumping to ensure complete oxidation of polymer molecules.

Note: For high viscosity slurry or slurry that has been pre-treated with DE-CHLOR a higher dosage of SLURRY BUSTER DRY may be necessary.

PACKAGING:

15 lb pail, 36 per pallet. All pallets are plastic-wrapped..

North America: 847.851.1800 | 800.527.9948

UPDATED: OCTOBER 2013



