

SODIUM BICARBONATE

NEUTRAL PH BUFFER

DESCRIPTION

SODIUM BICARBONATE, NaHCO_3 is used to lower the pH of drilling slurry from a pH of 12-13 (alkaline) to a neutral pH range of 8-9. A white powder, SODIUM BICARBONATE is also added to a base drilling fluid as a pH neutralizing additive. A buffer, SODIUM BICARBONATE is added to acidic water to raise the pH to 8-9.

RECOMMENDED USE

SODIUM BICARBONATE is used to treat cement contamination in SHORE PAC drilling slurry and bentonite water based drilling fluids. It is also used as a buffer. SODIUM BICARBONATE will remove calcium and manganese making hard water soft.

CHARACTERISTICS

- Easy to mix and use, soluble in water
- Economical method to lower pH
- Safe to use, noncombustible

MIXING AND APPLICATION

SODIUM BICARBONATE should be added to the mixing water prior to mixing the primary drilling product. SODIUM BICARBONATE dissolves readily in water. Add slowly through a hopper at a ratio of 5 lbs per 1,000 gallons mix water.

CHARACTERISTICS

Appearance	White powder
Solubility	7.8 g/100 g water @ 64 °F (18 °C)
pH (1% solution)	8.3
Density	2.2

PACKAGING

50 lb bags, 49 bags per pallet.

North America: 847.851.1800 | 800.527.9948

© 2013 CETCO. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit www.CETCO.com. CETCO accepts no responsibility for the results obtained through application of this product. CETCO reserves the right to update information without notice.

UPDATED: OCTOBER 2013

TDS_SODIUMBICARBONATE_AM_EN_201310_v1

CETCO®

An **AMCOL** Company

www.CETCO.com