

SODIUM HYDROXIDE

DRY PELLET PH REGULATOR

DESCRIPTION

SODIUM HYDROXIDE, NaOH, is a white solid sold in pellet form. SODIUM HYDROXIDE is completely ionic, containing sodium ions and hydroxide ions. The hydroxide ions make SODIUM HYDROXIDE a strong base which reacts with acids to form water and salts. This is what controls the pH of SHORE PAC slurry when drilling in acidic organic peat soil and brackish salt-impacted soil. SODIUM HYDROXIDE is also an alkaline metallic base, making it an ideal pre-treatment additive to enhance flocculation of solids with the INSTA-CLEAR DRY additive.

RECOMMENDED USE

SODIUM HYDROXIDE is used in SHORE PAC slurry systems to regulate and treat pH. SHORE PAC foundation drilling slurry performs at maximum levels with the right pH of 8-10. SODIUM HYDROXIDE controls pH of SHORE PAC slurry when drilling in contaminants such as acid peat soils (organics), hard water (450 ppm), and soil saturated with sea water.

CHARACTERISTICS

- Odorless white solid (pellets)
- pH (1% solution): 13.6
- Weight/Gallon: 12.7-12.8 lbs
- High solubility in water: 111 g/100 ml (20°C)
- Specific Gravity: 2.12 g/cm³ solid

MIXING AND APPLICATION

Add SODIUM HYDROXIDE to slurry make-up water before adding SHORE PAC polymer. Dosage will vary with type and quality of make-up water and presence of soil contaminants such as acidic organic peat soils and evaporate salt formations. Typical freshwater usage rates are 2.5 to 5.0 lbs per 1,000 gallons make-up water. SODIUM HYDROXIDE dissolves readily in water. Add slowly through a hopper at a ratio of 5 lbs per 1,000 gallons mix water.

ADVANTAGES

STORAGE:	No freeze concerns with dry pellets
DRY SOLID:	No splashing "glugging" liquid burn hazards
PELLET SHAPE:	No wind blown particles reducing eye threat
ECONOMICAL:	Versus liquid, the dry pellets cost less and perform better
EASY TO USE:	Very soluble in water with liberation of heat
DOSAGE RATE:	2.5 to 5.0 lbs per 1,000 gallons makeup water

PACKAGING & PERSONAL SAFETY

55 lb, multi-wall plastic airtight bags, 40 bags per pallet. The dry pellet form of SODIUM HYDROXIDE reduces the chance of chemical burn hazards from handling and wind blown particles, however, it is a strong alkali and workers should wear chemical goggles when handling, along with rubber gloves. Refer to MSDS for additional safety information.

North America: 847.851.1800 | 800.527.9948

© 2013 CETCO. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit www.CETCO.com. CETCO accepts no responsibility for the results obtained through application of this product. CETCO reserves the right to update information without notice.

UPDATED: OCTOBER 2013

TDS_SODIUMHYDROXIDE_AM_EN_201310_v1

CETCO®

An **AMCOL** Company

www.CETCO.com