

Air Tools - Chipping Hammers



Real Tools. Real Work.

Toku's rugged TCH series of "D-handle" chipping hammers are available in 2" through 4" stroke lengths. All TCH series chipping hammers feature drop forged handles, replaceable bushings, heat treated alloy cylinders, and exhaust deflectors. The TCH line of hammers features a rock solid four bolt handle for maximum reliability and durability which allows a sure grip in all conditions. The TCH series is designed to only operate when the chisel is in contact with the work surface to avoid excessive wear caused by dry firing.

Toku's AA-0S chipping hammer proves bigger is not always better. It's lightweight and compact size allows for greater flexibility when working in tight spaces or small enclosures. The AA-0S is small on size but big on power.



	AA-0S	TCH-2	TCH-3	TCH-4
Shank Size	.680" Round Shank or .580" Hex Shank with Round or Oval Collar (Please Specify)			
Piston Stroke	1-13/16" (45mm)	2" (50.8mm)	2-1/2" (63.5mm)	4" (101.6mm)
Piston Diameter	7/8" (22.2mm)	1-1/8" (28.54mm)	1-1/8" (28.54mm)	1-1/8" (28.54mm)
Impact Rate	3,000 - 3,200 BPM	2,600 - 2,800 BPM	2,000 - 2,200 BPM	1,600 - 1,800 BPM
Weight	7.9 lbs. (3.6 kg.)	18 lbs. (8.1 kg.)	19 lbs. (8.55 kg.)	20 lbs. (9 kg.)
Overall Length	12-3/4" (374.65mm)	14-3/4" (374.65mm)	16" (406.4mm)	17" (431.79mm)
Air Consumption	22.95 CFM	29.75 CFM	31.5 CFM	33.25 CFM
Air Inlet	3/8" NPT	7/8" x 24 Thrds/In NPT	7/8" x 24 Thrds/In NPT	7/8" x 24 Thrds/In NPT
Hose Size	1/2" (12.7mm)	1/2" (12.7mm)	1/2" (12.7mm)	1/2" (12.7mm)

Toku's THA series of gooseneck chipping hammers are available in 1" through 4" stroke lengths. The THA series utilizes a saw tooth connection between the handle and cylinder which provides a more secure, positive fit.

The Toku THA series chipping hammers feature alloy steel drop forged handles, replaceable bushings, heat treated alloy cylinders, reliable ring valve design, and exhaust deflectors. Optional quick connect retainers are available for all models.



	THA-1B	THA-2B	THA-3B	THA-4B
Shank Size	.680" Round Shank or .580" Hex Shank with Round or Oval Collar (Please Specify)			
Piston Stroke	1" (25.4mm)	2-3/32" (51mm)	2-17/32" (64mm)	4-1/32" (102mm)
Piston Diameter	1-1/8" (28.54mm)	1-1/8" (28.54mm)	1-1/8" (28.54mm)	1-1/8" (28.54mm)
Impact Rate	2,500 BPM	2,300 BPM	2,200 BPM	1,800 BPM
Weight	14.8 lbs. (5.9 kg.)	15.8 lbs. (6.2 kg.)	16.5 lbs. (6.8 kg.)	18.25 lbs. (7 kg.)
Overall Length	15-9/32" (388mm)	16-1/4" (413mm)	17-23/32" (450mm)	18-29/32" (480mm)
Air Consumption	28 CFM	29.75 CFM	31.8 CFM	33.25 CFM
Air Inlet	3/8" NPT	3/8" NPT	3/8" NPT	3/8" NPT
Hose Size	1/2" (12.7mm)	1/2" (12.7mm)	1/2" (12.7mm)	1/2" (12.7mm)

1-800-826-2672 P

www.tamcotools.com

724-258-6692 F